

Key Plant Adjustable Height Pipe Support



Photograph shows :
Hollow Bore 5 Ton Headstock with Adjustable Height Idler

The adjustable height idler is ideal to use in conjunction with positioners and headstocks on small diameter pipes and flanges. The advantage of using this particular design is that there is no need to pack up or raise a standard idler to suit different diameters of pipe. The overall height from the floor to the rotation wheels is adjustable through a leadscrew.

Machines are supplied with an option of a stationary or traversing under carriage base.

Capacity	-	2,000kg
Base length	-	900mm
Base width	-	500mm
Min overall height from rail to centre of wheels	-	690mm
Max overall height from rail to centre of wheels	-	1100mm
Elevation leadscrew stroke	-	410mm
Width of wheels	-	50mm
Overall diameter of wheels	-	150mm
Number of wheels per section	-	2
Type of wheels	-	Polyurethane or Steel
Rail centres	-	800mm
Traversing undercarriage wheels	-	4 off steel flanged 125mm OD - 42mm wide
Min – Max pipe diameter range	-	800mm

*(The minimum and maximum diameter range can
manufactured to suit customers requirement)*

Machine is fully guarded and C.E. approved and painted in Key Plant Red RAL 3020
1 off Operation & Maintenance Instruction Manual

Key Plant
Head Office
Regent Road
Liverpool
L3 7DS
Tel: 44 (0) 151 255 1800
Fax: 44 (0) 151 255 1900
Email: hire-sales@key-plant.co.uk

Key Plant
Works, Bode Business Park
Ball Hays Green
Leek, Staffordshire
ST13 6BW
Tel: 44 (0) 1538 388 388
Fax: 44 (0) 1538 381 509
Web: www.key-plant.co.uk